



MOLD RESISTANT COATING

FEATURES

- Resists mold growth on dry paint film
- Helps block severe stains
- Odor blocking
- Seals porous surfaces
- Promotes adhesion
- Hides previous colors
- Easy sanding
- Fast drying formula

RECOMMENDED USES

- Wood
- Sheetrock
- Masonry block
- Plaster
- Paneling
- Painted metal
- Wallboard
- Concrete



ERASE STAINS & SEAL ODORS FOR A PERFECT FINISH

Powerful stain blocking primer that will block most interior stains from mold, mildew, water, smoke, tannins, ink, grease, markers, and more. Also seals odors from pets, food, and smoke.

Our aerosol is ideal for small projects and spot priming interior surfaces including wood, drywall, plaster, paneling, wallpaper, masonry, brick, painted metal, and prepared glossy surfaces. Covers up to 10 square feet per 13oz can.

Available in: 13oz Aerosol Spray Can
Item #: BSBW-13oz
Case pack: 6

MADE IN THE USA

Distributed By: NatuReal, LLC 2091 NE 36th St #50548
Lighthouse Point, FL 33074 800.921.4634
bioesquesolutions.com



MOLD RESISTANT COATING

DIRECTIONS FOR USE

- The surface must be clean, free of dust, grease, wax, peeling paint, mold, mildew, and wallpaper paste. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.
- Peeling or Checked Paint: Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.
- Glossy Surfaces: For maximum adhesion, scuff sand the surface thoroughly before priming.
- For best results, use at room temperature.
- Cover adjacent areas to protect from overspray.
- Shake can vigorously for 1 minute after mixing ball begins to rattle and often during use.
- Hold can upright, moving from side-to-side while spraying lightly and evenly about 12" from area being painted.
- 2-3 thin coats produce best results.
- Can be topcoated with latex or oil-based paint after 60 minutes.
- Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released.
- If spray nozzle becomes clogged, remove and clean. Do not stick pins or wire into can opening.
- Replace nozzle with valve opening pointed away from you.
- Clean fresh overspray with mineral spirits or paint thinner. Remove dried paint with paint remover but test small area first to ensure paint remover does not damage substrate.
- Please consider donating any unused product.
- For recycling or disposal information, contact your local household refuse collection service.

PRECAUTIONARY STATEMENTS

- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
- Wear protective gloves, protective clothing and eye or face protection.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
- No smoking.
- Do not spray on an open flame or other ignition source.
- Use only outdoors or in a well-ventilated area.
- Do not breathe dust or mist.
- Do not eat, drink or smoke when using this product.
- Wash thoroughly after handling.
- Pressurized container: Do not pierce or burn, even after use.

DANGER!

- Extremely flammable aerosol.
- Contains gas under pressure; may explode if heated.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause drowsiness or dizziness.
- May cause cancer.
- Suspected of damaging fertility or the unborn child.
- Causes damage to organs through prolonged or repeated exposure.

PROPERTIES

Physical Form	Liquid/Aerosol
Odor	Not Available
Color	White
Flash Point (TCC)	-103 C (-153.4 F)
pH	N/A
Solubility	Not Soluble
DOT Shipping Label	UN1950 – Aerosols – Class 2.1
CA Prop 65	None
Shelf Life	2 Years
Density	.83 (6.93 lbs/gal)
Viscosity	>21 mm ² /s
CA Prop 65	Yes; Warning Cancer & Reproductive Harm –

Properties are typical and subject to usual manufacturing tolerances.

HEALTH & SAFETY INFORMATION:

Consult the Bioesque Solutions Safety Data Sheet for full details regarding Hazardous Properties and Personal Protective Equipment requirements.

MADE IN THE USA

Distributed By: NatuReal, LLC 2091 NE 36th St #50548
Lighthouse Point, FL 33074 800.921.4634
bioesquesolutions.com